

1. Unique identification code of the product-type:

CH-1500X CHARTER INTERIOR- EXTERIOR

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11, paragraph 4:

See the batch number on each package

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Coating for the protection and repair of Concrete:

.- dampness control

.- increased resistivity

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11, paragraph 5:

PINTURAS LEPANTO S.A.

CTRA. SAN ESTEBAN S/N

22500 BINÉFAR (HUESCA)

Tel: +34 974 428 339

Fax: +34 974 430 688

jllavori@pinturaslepanto.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12, paragraph 2:

N/A

6. System or systems of assessment and verification of the constancy of the performance of the construction product as set out in Annex V:

2 + (according to table ZA.1e)

7. In the case of a declaration of benefits in respect of a construction product covered by a harmonised standard:

European Standard EN-1504-2 of October 2004

Notified body: TECNALIA R&I CERTIFICACION. No. 1239

Task carried out: Issuance of the Evaluation of the Factory Production Control by the 2+ system and the Certificate of the Factory Production Control, 1239/CPR/0818401, dated 21/03/2017

DECLARATION OF PERFORMANCE

Nº DdP CH-1500X

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A

9. Declared performance

Essential characteristics (see Note 1)	Performance (see Note 2)	Harmonised technical specifications (see Note 3)
Linear retraction	NPD	EN 1504-2:2004
Thermal expansion coefficient	NPD	
Lattice cutting	NPD	
CO2 permeability	S_D > 50	
Water vapour permeability	Class 1: S_D < 5m	
Capillary absorption and water permeability	W < 0.1 kg/m² · h^{0.5}	
Thermal compatibility	NPD	
Resistance to cracking	NPD	
Adhesion by pull-off test	Rigid Systems: ≥ 2.0 N/mm²	
Reaction to fire	B-s1, d0.	
Slip resistance	NPD	
Artificial ageing	NPD	
Anti-static behaviour	NPD	
Adhesion on wet concrete	NPD	
Hazardous substances		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Alfonso Ruiz Baró (CEO)

Binéfar, April 4, 2017